



# Antimicrobial Floor Finish AR



	<b>Alcohol Resistant</b>
<b>Compatible with the Altra Lite Applicator</b>	<b>MICROBAN</b> <small>PROTECTION THAT LIVES ON</small>

Altra Antimicrobial Floor Finish AR utilizes Microban® antimicrobial technology, providing 24/7 protection to help inhibit the growth of bacteria on floors. Altra Antimicrobial Floor Finish AR is formulated with proprietary Renaissance Performance Polymers and offers unique attributes such as alcohol resistance, clarity, durability, and reparability. Fast-drying for healthcare environments, Altra Antimicrobial Floor Finish AR is the prescribed choice for refinishing hospital hallways and rooms efficiently.\*



**Alcohol resistant**



**Applicator friendly**



**Formulated with Microban® Technology**

\*Microban technology does not protect users against disease-causing microorganisms. Microban Products Company makes neither direct nor implied public health claims. Normal cleaning practices should be maintained.

## Directions for use

### Floor Preparation:

1. Strip floor using Altra Low Odor Floor Stripper.
2. After picking up solution, rinse floor until no residue remains.
3. Allow floor to dry before applying Altra Antimicrobial Floor Finish AR.

### Application:

1. Apply finish in even coats 750 sq. ft./48 oz.
2. Allow each coat to dry, usually 20 to 30 minutes.
3. Apply multiple coats until desired gloss is achieved.

### Using Altra Lite Applicator:

1. Use an Altra Lite applicator with a clean and rinsed microfiber finish mop.
2. Saturate microfiber finish mop with water and ring out prior to applying finish.

### Using Standard String Mop:

1. Use a clean mop and bucket with a new trash liner.
2. Saturate mop, press firmly into wringer to remove excess finish. Do not wring mop.

### Maintenance:

1. Dust mop floor.
2. Damp mop floor as needed, using Altra Multi-Purpose HP Cleaner.

Altra Antimicrobial Floor Finish AR Technical Specifications	
pH	8.4 ± 0.2
Leveling	Excellent
Odor	Low
Freeze/Thaw Stability	Passes 3 cycles
Removability	Excellent
Dry Time	20–25 minutes
Alcohol Resistance	Good–Excellent
Black Mark Resistance	Excellent
Film Color	Water-Clear
Scrubability	Excellent
Weight/Gallon	8.53 lbs.
Slip Resistance	UL Classified

Made in USA



Available Packaging	Coverage
8 × 48 oz. bottle	750 sq ft – 1000 sq ft per cartridge
2 Gallon Mini Pac	2000 sq ft – 2600 sq ft per gallon