



Altra Lift™

Specialty Coating Remover



*Mild pH coating remover
designed for specialty floors*

DILUTION RATIO 1:16 for 5 –15 coats



Altra Lift is a Green Seal Certified® cold water floor coating remover designed to remove finishes and seals from all flooring types in one application. It contains no hazardous ingredients like butyl, eliminating noxious odors and making application safer for workers. Its low odor and effective formulation make it easy to remove coatings, causing less disruption for staff, visitors, and patients.



Mild pH



**Designed for
specialty floors**



Low odor

Directions for use

(For use in COLD water)

Routine Removal:

Use 8 fl. oz./gallon water (64 ml/l), (1:16).

Heavy Duty Removal:

Use 16 fl. oz./gallon water (125 ml/l), (1:8).

1. Apply diluted Altra Lift to the floor. Allow to stand 10–15 minutes on the floor depending on the number of coats needed to be removed.
2. Machine scrub.
3. Pick up solution. Do not allow solution to dry on the floor.
4. Rinse the floor at least twice with cold water.
5. After the floor is dry, apply a Green Seal Certified floor coating.

Note: Ensure adequate ventilation, especially in confined areas.

Available Packaging: 8 × 32 oz. Quart bottle

Altra Lift Environmental Floor Coating Remover Technical Specifications	
Total Actives	28.035%
pH Concentrate	10.5 ± 0.2
pH (1:8)	10.1 ± 0.2
Weight/Gallon	8.5 lbs
Color	Water White, Clear
Fragrance	No added perfume
Hard Water Stability (1:80 with 350ppm hard water)	Clear
Rinsing Properties	Excellent
Foaming Properties	Low
Green Seal™ Certification	Yes

Made in USA



Improper use and dilution may result in inadequate cleaning and may result in health and physical hazards that match those of the concentrate. When handling concentrated product wearing safety glasses and gloves is suggested.

Dispose of unused product and solutions in accordance with local, state and federal regulations.

Please recycle empty container.