



Altra Preserve™

Strip-free Floor Coating



FLOOR CARE

Protect & Restore Specialty Flooring

Compatible with the
Altra Lite Applicator

PROTECTION THAT LIVES ON
MICROBAN®

Specialty flooring requires specialty maintenance. Rethink standard floor maintenance with Altra Preserve.

Altra Preserve is a strip-free floor coating formulated to extend the life of specialty flooring, including LVT. It protects the floor, creating a soft, more natural look. Altra Preserve also utilizes Microban® antimicrobial technology to inhibit the growth of bacteria on floors. Through careful manipulation of particle size and distribution, Altra has designed polymers and a resin system that eliminates floor stripping, prevents heavy build up, and makes floors easier to clean. Altra has solutions where it matters.



**Protects
and restores**



**Formulated with
Microban® Technology**



**No floor stripper
required**

Directions for use

Preparation

Automatic scrubber

1. Dust mop or use a tack cloth to remove heavy dirt or soils.
2. Scrub the floor using Altra Heavy Duty Cleaner and pick up solution.

Mop and bucket or microfiber pad

1. Dust mop or use a tack cloth to remove heavy dirt or soils.
2. Mop the floor with Altra Heavy Duty Cleaner. Change microfiber pad as needed for heavily soiled surfaces. No rinse required.

Application

New application

1. Follow preparation steps above.
2. Apply 2-3 coats of undiluted product with an Altra Lite applicator and a rinsed microfiber pad or damp mop.
3. Allow 15 minutes for drying and then repeat application. Do not rinse.

Routine Maintenance

1. Sweep large debris with a dust mop or tack cloth.
2. Damp mop daily with Altra Multi-Purpose HP Cleaner to maintain a uniform look. You may also use an automatic scrubber with a white or red pad and Altra Multi-Purpose HP Cleaner to maintain a uniform look.
3. Recoat with Altra Preserve based on traffic recommendations below:
Light Traffic – Monthly or as needed
Moderate Traffic – Monthly or every 2 weeks
Heavy Traffic – Weekly or every 2 weeks

Restorative Maintenance

1. Follow new application steps above.
2. Recoat recommendations based on traffic recommendations below:
Light Traffic – Yearly
Moderate Traffic – Every 6 months
Heavy Traffic – Quarterly or as needed

Altra Preserve Technical Specifications	
pH	8.4 ± 0.4
Leveling	Excellent
Freeze/Thaw Stability	Passes 3 cycles
Removability	Excellent
Drying Time	10–15 minutes
Dirt Resistance	Excellent
Film Color	Water-Clear
Weight/Gallon	8.41 lbs.
Slip Resistance	UL Classified

Made in USA



Available Packaging: 8 × 48 oz. bottle
2 Gallon Mini Pac